

## Ice Melting Compounds

## Do you live in one of the five snowiest cities in the U.S.?1

- + Truckee, Calif. 202.6 inches of snowfall annually
- $\cdot$  Steamboat Springs, Colo. 179.6 inches of snowfall annually
- $\cdot$  Oswego, N.Y. 141.0 inches of snowfall annually
- Syracuse, N.Y. 123.8 inches of snowfall annually
- Marquette, Mich. 117.2 inches of snowfall annually

Even if you don't, chances are good if you live in any of the lower 48 states, you'll probably experience snow or ice at one time or another this winter. In fact, on Jan. 11, 2011, there was snow recorded in 49 of the 50 states — the only state spared at that time was Florida.

There are many ways to deal with snow and ice, from plowing and shoveling to scraping and using ice-melting compounds. This document addresses the advantages and disadvantages of the different ice-melting options available.

<sup>1</sup> Source: WeatherDB.com

UnitedHeartland.com 1-800-258-2667 UHUnitedHeartland

Part of the AF Group

United Heartland is the marketing name for United Wisconsin Insurance Company, a member of AF Group. All policies are underwritten by a licensed insurer subsidiary of AF Group.



The science behind these products is such that throwing more ice-melt compound on the ice won't help it melt faster; it will just waste resources. The compound will not dissolve or melt and will simply be dragged into buildings and cars or affect landscaping. Here are some key points to keep in mind:

- Ice-melt compounds are only effective down to specific temperature limits that vary by compound. Know these temperatures, referred to as eutectic temps, and monitor them to ensure effective use of your ice-melt compound. Remember, adding additional ice-melt compound to areas already welltreated will be simply wasting compound.
- Periodically inspect areas where ice-melt compound has been spread

   has the melting action of the compound been reduced as the solution concentration has changed? Should more compound be spread to increase the solution concentration?
- The higher the air temperature, the more effective the melting action of the ice-melt compound. Knowing the outdoor air temperature and the lowest temperature for effective use of your ice-melt compound should guide you when ice-melt should be applied to walking surfaces and up to what point it will no longer be effective.
- The temperature of the air, pavement, and the type of ice-melt compound used will affect the rate at which the ice melts.

There are many different ice-melt compounds available from traditional rock salt (sodium chloride) to ice-melt pellets (calcium chloride). Each compound has unique properties and costs that should be factored in when determining what ice-melt compound is best for your use.


Both sodium chloride and calcium chloride can be acquired in bulk quantities at relatively low cost. The disadvantage of these compounds is they tend to be corrosive to concrete or steel and can be harmful to vegetation. However, other less corrosive or less toxic compounds tend to be more expensive and may make it more difficult to treat needed areas.

## Wondering what the science behind ice-melt is?

Ice-melting compounds lower the freezing point of water. These products attract moisture to themselves to form a liquid brine solution which can generate heat and melt the ice. The amount of ice that is melted by a given quantity of ice-melt compound will decrease as the temperature of the mixture is lowered. As the ice melts, the compound solution's concentration is reduced and the freezing point of the water starts to increase until such time that more ice-melt compound is spread on the ice and water.

The lowest melting point of the water and ice-melt compound solution is termed the "eutectic" temperature. At this limiting eutectic temperature, solutions of the ice-melt compound aren't effective and the melting action on the ice will cease.

The quantity of ice-melt compound needed to lower the freezing point of ice to the eutectic temperature is called the "eutectic concentration." At this lowest temperature, the rate at which ice melts is very slow. When this melting action slows, adding more compound has no impact on lowering the eutectic temperature, thus, the ice melts no faster.



## Knowing what to use

It's important that your organization assess your needs for application of ice-melt compounds. Consider the areas to be covered, access to traffic and sunlight, (which improve the effectiveness of ice-melt compounds), methods for treating needed areas, and cost. The chart below offers some guidance on materials to consider, as well as pros and cons for each compound.

| Туре   | Uses  | Advantages  | Disadvantages  | Notes   |
|--|---|---|--|---|
| Sodium Chloride<br>(Rock Salt) — NaCl                                | <ul> <li>Plain</li> <li>Wet with<br/>CaCl2</li> <li>Wet with<br/>NaCl brine</li> </ul>                    | • Low purchase price  | <ul> <li>Can be corrosive to concrete,<br/>structural steel in bridges<br/>and cars.</li> <li>Potentially harmful to<br/>roadside vegetation.</li> <li>Can contaminate surface<br/>water and drinking water<br/>supplies.</li> </ul> | <ul> <li>Workhorse of de-icing chemicals.</li> <li>Works to 15°F</li> </ul>   |
| Sodium Chloride<br>(Salt), Brine — NaCl                              | <ul> <li>Pre-wetting<br/>other<br/>chemicals</li> <li>Anti-icing</li> </ul>                               | <ul> <li>Low purchase price</li> <li>Little to no residue<br/>on pavement</li> <li>Doesn't draw<br/>moisture and leave<br/>road wet and slick</li> </ul>  | <ul> <li>Can be corrosive to concrete,<br/>structural steel in bridges<br/>and cars.</li> <li>Potentially harmful to<br/>roadside vegetation.</li> </ul>   | <ul> <li>Used primarily as pre-<br/>wetting and/or anti-icing<br/>agent</li> <li>Works to 15°F</li> </ul>   |
| Calcium Manganese<br>Acetate (CMA) —<br>Ca(O2CCH3) 2<br>Mg(O2CCH3) 2 | <ul> <li>CMA liquid<br/>mixed with<br/>salt or sand</li> <li>Liquid alone</li> </ul>                      | <ul> <li>Less corrosive than<br/>salt</li> <li>Reduces corrosion on<br/>steel bridges</li> </ul>  | <ul> <li>Need to use twice as much<br/>CMA as salt</li> <li>High concentrations can<br/>reduce oxygen levels in<br/>streams and lakes</li> <li>Pavement appears wet</li> </ul>   | <ul> <li>Best product available<br/>from an environmental<br/>standpoint</li> <li>Works to 15°F</li> </ul>  |
| Magnesium Chloride<br>— MgCl2  | <ul> <li>Sprayed<br/>directly on<br/>road</li> <li>Mixed with<br/>sand or other<br/>de-icers</li> </ul>   | <ul> <li>Attracts moisture<br/>from the air, which<br/>hastens dissolving<br/>and melting</li> <li>Does not require<br/>post distribution<br/>cleanup</li> <li>Doesn't appear to<br/>contribute to air<br/>pollution</li> </ul> | <ul> <li>Keeps pavement wet if it<br/>attracts too much moisture<br/>from the air</li> <li>Cost</li> <li>Corrosive to metal</li> </ul>   | <ul> <li>Liquid used as an anti-<br/>icing agent when air<br/>temperatures exceed 10°F</li> <li>Can be applied to busy<br/>streets and intersections<br/>before light snow storms<br/>to melt snow as it hits the<br/>pavement</li> <li>Works to -13°F</li> <li>Costs approximately two<br/>times more than salt</li> </ul> |
| Calcium Chloride —<br>CaCl2  | <ul> <li>Used as a pre-<br/>wetting agent<br/>for solids like<br/>sand, salt,<br/>urea, or CMA</li> </ul> | <ul> <li>Requires fewer<br/>applications</li> <li>Performs very well</li> <li>Safer than salt for<br/>structural steel and<br/>reinforcing steel</li> <li>Noncorrosive,<br/>biodegradable</li> </ul>                            | <ul> <li>Cost</li> <li>Could cause slickness on<br/>pavement</li> <li>Lowers oxygen levels in<br/>bodies of water</li> </ul>   | <ul> <li>Liquid works best as a deicer if applied in narrow bands</li> <li>May be used alone if needed</li> <li>Works to -75° F</li> <li>Costs approximately eight times more than salt</li> </ul>  |
| Carbohydrate-based<br>solution (corn- or<br>beet- based)             | <ul> <li>Liquid<br/>typically<br/>mixed with<br/>MgCl2 and<br/>other salts</li> </ul>                     | <ul> <li>Cost</li> <li>No adverse effects<br/>on roads and<br/>infrastructures</li> <li>Corrosion inhibitor</li> </ul>  | <ul> <li>Some products may have an odor</li> </ul>   | <ul> <li>Liquid is thick</li> <li>Biologically and<br/>environmentally safe</li> <li>Contains agricultural by-<br/>products</li> </ul>  |
| Sand   | • Provides<br>traction  | • Cost  | <ul> <li>Cleanup cost of sediment in<br/>storm drains</li> </ul>   | <ul> <li>Some products are<br/>available that have a mix<br/>of other de-icing materials<br/>and sand</li> </ul>  |

\* Chart adapted with permission from: Technology News, August 1995, Iowa Transportation Center, Iowa State University; "Safer De-icing Chemicals - Home Steading." Mother Earth News, December 2003; and the University of Minnesota Extension Service Yard & Garden Brief: Effects of De-icers on Trees and Shrubs.



Founded in 1912, AF Group (Lansing, Mich.) and its subsidiaries are a premier provider of innovative insurance solutions. Rated "A-" (Excellent) by A.M. Best, AF Group is a nationally recognized holding company conducting business through its brands: Accident Fund, United Heartland, CompWest and Third Coast Underwriters.